



### Feature

1. Color R, G, B LCD type
2. 320RGBx240 dots
3. 8-bit data bus
4. Built-in White backlight (CCFL)
5. +3~+5V power supply.
6. 1/240 duty cycle

### Mechanical Data

Item	Standard Value	Unit
Module Dimension	154.6x114.8x8.5	mm
Viewing Area	118.18x89.38	mm
Dot Size	0.09 x 0.33	mm
Dot Pitch	0.12 x 0.36	mm

### Pin Assignment

Pin	Symbol	Function
1	FRM	Scan start-up signal
2	LOAD	Data latch
3	CP	Data shift
4	DISP	Display enable signal
5	VDD	Power supply to logic
6	VSS	Ground
7	VEE	Power supply for LCD
8	DB7	Display data bus
9	DB6	Display data bus
10	DB5	Display data bus
11	DB4	Display data bus
12	DB3	Display data bus
13	DB2	Display data bus
14	DB1	Display data bus
15	DB0	Display data bus

### Absolute Maximum Rating

Item	Symbol	Standard Value			Unit
		min.	typ.	max.	
Power Supply	VDD-VSS	2.7	3.0	3.3	V
Input Voltage	VI	4.7	5.0	5.3	V
		0.8V <sub>DD</sub>	--	VDD	V

Note: VSS=0 Volt, VDD=5.0 Volt.

### Electronical Characteristics

Item	Symbol	Condition	Standard Value			Unit
			min.	typ.	max.	
Input Voltage	VDD	L level	0.8V <sub>DD</sub>	--	V <sub>DD</sub>	V
	VIO	H level	0	--	0.2V <sub>DD</sub>	V
Supply Current	IDD	VDD=+5V	--	--	--	mA
Recommended LC Driving Voltage for Normal Temp. Version module	VDD-V0	0°C	--	--	--	V
		25°C	--	26.2	--	
		50°C	--	--	--	
Power consumption	VFLS	25°C	--	2.0	--	mA